



OLYMPUS

GENERAL SPECIFICATIONS

Width	54"
Weight	36 oz/linear yard
Roll Size	30 yds
Composition	100% PVC
Backing	100% Spun Polyester Terry Loop

RECOMMENDED APPLICATIONS



FLAME RETARDANCY SPECIFICATIONS

CAL-TB 117-2013	Passes
NFPA 260	Passes
FMVSS 302	Passes
UFAC Class 1	Passes
BIFMA Class A	Passes
IMO Part 8 (3.1 & 3.2)	Passes

CLEANING INSTRUCTIONS

Remove ordinary dirt and smudges with a mild soap and water solution and a clean, soft cloth or towel. Dry with a soft, lint-free cloth or towel. CAUTION: The use of vinyl "conditioners" or "protectants" is not recommended and should be avoided on vinyl treated with PreFixx® protective finish.

To clean difficult stains, locate the staining agent in the list below and follow the corresponding recommended cleaning method. For best results, treat stains immediately. Cleaning Tip: to determine the method and type of cleaners, the source of the stain should be identified.

Type of Stain:

Baby oil, ketchup, chocolate, motor oil, olive oil, grape juice, blood, tea, coffee and betadine, use **Method 1**
Eye shadow, crayon and grease, use **Method 1**, if stain remains, use **Method 2**
Tobacco tar (nicotine), permanent felt marker, yellow mustard, lipstick, ballpoint pen and spray paint, use **Method 1**, if stain remains, use **Method 2** and for remaining stubborn stains use **Method 3**

Method 1: Clean area with Formula 409® All-Purpose Spray Cleaner or Fantastik® Spray Cleaner, using a soft cloth or damp sponge, rinse area with fresh water, then dry with a clean lint-free cloth.

Method 2: Use a solvent-type cleaner, such as rubbing alcohol (isopropyl alcohol). Rinse cleaned area with fresh water, then dry with a clean lint-free cloth.

Method 3: Use a strong, active solvent cleaner diluted in water (70% water/30% solvent cleaner) such as acetone based nail polish remover (acetone/water). Clean with a soft cloth or damp sponge. Stain should be removed with less than 6 rubs. If the stain persists after 6 rubs, the stain has set and probably cannot be removed. Rinse area with fresh water, then dry with a clean, lint-free cloth.

PERFORMANCE SPECIFICATIONS

Abrasion	1,800,000+ DR
Cold Crack	-20°
UV Resistance	650 Hours
Mildew Resistance	Yes
Sulfide Stain Resistant	Yes